

PRODUCT DATA SHEET

STAIR NOSINGS

Cleartread 50TP35

Clearview offers a comprehensive range of architecturally designed profiles to meet every demand, from heavy duty traffic in railway stations to the more general retail/office use, providing maximum pedestrian safety and WHS requirements. Clearview Stair Nosings are manufactured to meet and exceed the Australian standards and building codes.

SPECIFICATIONS

PRODUCT	Cleartread Stairnosing
CODE	50TP35
MATERIAL	Alloy: 6060, Temper: T5
INSERT TYPE	Santoprene
OVERALL DIMENSIONS	85mm x 35mm
PRODUCT WARRANTY	4 years (As per Clearview's Standard Warranty)
SLIP RATING	P3
CODE COMPLIANCE	AS/NZS1428.4.1:2009, BCA 2014 (Subject to surrounding floor finish luminance)
FIXING METHOD	Screw fixed

PROFILE



STANDARD COLOURS

Insert

BI ACK

Aluminium



CLEAR ANODISED






GOLD ANODISED

TYPICAL INSTALLATION

Screw fixed



HOW TO SPECIFY

Copy the prewritten specification below and update all sections in brackets to create your project specification.

Description

Description
Clearview Stairnosing Profile in Code: 50TP35
in (Clear/Black/Sovereign Gold) anodised finish
aluminium with insert colour (BLK/Y/G/WH). To
be installed to the manufacturer's instructions in
accordance to the AS/NZS 1428.1.4.2009

Manufacturer Clearview Tactiles P: 1300 884 948

E: sales@clearviewtactiles.com.au
W: www.clearviewtactiles.com.au

Example - Typical Specification

Clearview Stairnosing Profile in Code: 50TP35 in Clear anodised finish aluminium with insert

To be installed in accordance to the manufacturer's instructions in accordance to the AS/NZS 1428.1.4.2009







SAFETY YELLOW

WHITE

